

AN ISO 9001 CERTIFIED COMPANY

TECHNO ELECTRO POWER INDUSTRIAL W.L.L.

Distribution Boards LV Control Panels



PRODUCT CATALOGUE



Live Smart

www.tepgi.com

"At TEP Group International, we devise solutions that make a difference. Our safe, efficient, and reliable products are designed to improve the quality of life of our customers. Our unique capabilities make us the perfect players to revolutionize how we live, and we work towards that goal every day."

About Us

Established in 2004, TEP Group International started as a trading company in Bahrain and has become a global name in the manufacturing and distribution of high-quality electrical products and solutions in our field. We build trust with our clients, stakeholders and suppliers by maintaining a high-level business ethics and relationships.

With our center of operations located in the Kingdom of Bahrain and extended to the US and India, we represent several global and TEP brands including local and international governmentapproved electrical products distributed throughout the world to meet clients' obligations with the utmost confidence. For almost two decades, we have maintained our market reputation through our state of-the-art manufacturing factory, boasting 4,000 sqm. of facilities situated locally and internationally.

Armed with professionally qualified team with a diverse background, we are able to innovate and improve processes to provide safe and sustainable products of high quality.

Warranty Policy: Warranted against defects arising out of manufacturing processes or use of defective raw materials for a period of 18 months from the date of supply or 12 months from the date of installation whichever is earlier. The company reserves the right to either replace or repair the defective items after ascertaining the facts through a detailed service report on usage of our products in normal conditions.

Contents

1. Distribution Boards (DB)	1
2. SPN MCB DB Non–Split	2
3. SPN MCB DB Split	3
4. TPN MCB DB Non-Split	4
5. TPN MCB DB Split	5
6. TPN MCB DB Split (3 Row DBS)	6
7. Approvals & Certifications	7



Distribution Boards (DB)





Salient Features

- Aesthetically designed incompliance with latest standards
- Wide range of sheet-steel DBs up to 18ways
- SPN, TPN MCB Distribution Board
- Degree of protection IP30 as Standard
- IP31, 42 , IP43 & 55 available (non-Standard sizes)
- Surface & flush mounting
- Powder coated Corrosion & scratch resistant
- Detachable gland plate (optional)
- Adequate knock-outs on all sides
- Generous wiring space
- Clear circuit identification
- Supplied complete with busbar, earth & neutral bars
- Suitable for Ambient temperature 55 Degree



Technical Details

Voltage	240 V AC for SPN, 415 V for TPN DBs
Busbar Rating	63A/100A/125A
No. of Ways	4, 6, 8, 10, 12, 14, 18ways
Mounting	Surface/Flush
Di electric Strength	2.5kV RMS AC for 1 Min
Mounting Arrangement	35mm DIN Rail for MCBs, RCCBs (SPN) 125A
	Pan-tray assembly For TPN DB





SPN MCB DB Non–Split



Salient Features

- Single door
- IP30 protection
- Standard color RAL-7035
- Hinged full door with sliding lock
- Knock outs at Top, Bottom, Sides and back of enclosure
- Surface or Flush mounted covers
- · Generous wiring space, adequate for cable glands
- Superior powder coated finish for better protection against heat & dust (Powder coating thickness of more than 60 microns)
- Detachable gland plates (OPTIONAL)
- Complete with copper phase comb-bar, earth bar & neutral bars



Ordering Details

Code	Item	н	W	D
5114004	4 WAY SPN	200	270	90
5114003	6 WAY SPN	200	300	90
5114002	8 WAY SPN	200	340	90
5114005	10 WAY SPN	200	380	90
5114006	12 WAY SPN	200	420	90



All Dimensions are in Millimetre (mm)

a

SPN MCB DB Split



Salient Features

- Single door
- IP30 protection
- Standard color RAL-7035
- Hinged full door with sliding lock
- Knock outs at Top, Bottom, Sides and back of enclosure
- Surface or Flush mounted covers
- Generous wiring space, adequate for cable glands
- Superior powder coated finish for better protection against heat & dust (Powder coating thickness of more than 60 microns)
- Detachable gland plates (OPTIONAL)
- Complete with copper phase comb-bar, earth bar & neutral bars



Ordering Details

8

Code	Item	н	W	D
5114015	2+2 WAY SPN	330	230	90
5114007	4+2 WAY SPN	330	230	90
5114008	6+2 WAY SPN	350	270	90
5114009	6+4 WAY SPN	350	270	90
5114010	8+4 WAY SPN	350	300	90
5114011	8+6 WAY SPN	350	300	90
5114012	10+4 WAY SPN	350	340	90
5114000	10+6 WAY SPN	350	340	90



in Millimetre (mm)

TPN MCB DB Non-Split



Salient Features

- Single door
- IP30 protection
- Standard color RAL-7035
- Hinged full door with sliding lock
- Knock outs at Top, Bottom, Sides and back of enclosure
- Surface or Flush mounted covers
- Generous wiring space, adequate for cable glands
- Superior powder coated finish for better protection against heat & dust (Powder coating thickness of more than 60 microns)
- Detachable gland plates (OPTIONAL)
- With 125A Busbar Modular Interior



Ordering Details

Code	ltem	н	W	D
5126014	2 WAY TPN	380	390	100
5126006	4 WAY TPN	430	390	100
5126016	6 WAY TPN	480	390	100
5126017	8 WAY TPN	540	390	100
5126007	10 WAY TPN	600	390	100
5126018	12 WAY TPN	650	390	100



All Dimensions are in Millimetre (mm)

TPN MCB DB Split





Salient Features

- Single door
- IP30 protection
- Standard color RAL-7035
- Hinged full door with sliding lock
- Knock outs at Top, Bottom, Sides and back of enclosure
- Surface or Flush mounted covers
- Generous wiring space, adequate for cable glands
- Superior powder coated finish for better protection against heat & dust (Powder coating thickness of more than 60 microns)
- Detachable gland plates (OPTIONAL)
- With 125A Busbar Modular Interior

Ordering Details

Code	Item	н	W	D
5126012	2+2 WAY TPN	550	390	100
5126010	4+2 WAY TPN	600	390	100
5126019	4+4 WAY TPN	650	390	100
5126005	6+2 WAY TPN	650	390	100
5126009	6+4 WAY TPN	700	390	100
5126033	6+6 WAY TPN	760	390	100
5126011	8+2 WAY TPN	700	390	100
5126022	8+4 WAY TPN	760	390	100
5126013	8+6 WAY TPN	820	390	100
5123052	8+8 WAY TPN	870	390	100
5126035	10+2 WAY TPN	760	390	100
5126008	10+4 WAY TPN	820	390	100
5126000	10+6 WAY TPN	870	390	100



TPN MCB DB Split (3 Row DBS)



Salient Features

- Single door
- IP30 protection
- Standard color RAL-7035
- Hinged full door with sliding lock
- Knock outs at Top, Bottom, Sides and back of enclosure
- Surface or Flush mounted covers
- Generous wiring space, adequate for cable glands
- Superior powder coated finish for better protection against heat & dust (Powder coating thickness of more than 60 microns)
- Detachable gland plates (OPTIONAL)
- Complete with Copper phase comb-bar, earth bar & neutral bars

Ordering Details

Code	Item	н	W	D
5140000	2+2+2 WAY TPN	750	450	100
5140001	4+4+4 WAY TPN	900	450	100
5140002	6+6+6 WAY TPN	1060	450	100
5140003	8+8+8 WAY TPN	1230	450	100
5140004	4+2+2 WAY TPN	795	450	100
5140005	4+4+2 WAY TPN	850	450	100
5140006	6+6+2 WAY TPN	960	450	100
5140007	6+6+4 WAY TPN	1015	450	100
5140008	6+4+2 WAY TPN	910	450	100
5140009	6+4+4 WAY TPN	960	450	100
5140010	8+6+2 WAY TPN	1015	450	100
5140011	8+4+2 WAY TPN	960	450	100
5140012	8+4+4 WAY TPN	1010	450	100
5140013	8+8+4 WAY TPN	1110	450	100
5140014	8+8+6 WAY TPN	1175	450	100
5140015	10+4+2 WAY TPN	1015	450	100
5140016	10+4+4 WAY TPN	1070	450	100
5140017	10+6+4 WAY TPN	1121	450	100
5140018	10+8+4 WAY TPN	1175	450	100



All Dimensions are in Millimetre (mm)

Approvals & Certifications









	intertek		intertek Tat Darla Award	CAT	a fi
	CERTIFICATE	Αςται	YPE CERTIFICATE	ERTIFICAT	CERTIFICATE
VERIFICATION OF T		VERIFICATIO		U U	This is to Certify that the Management System of
Project No: G10466907	LCS002 Certificate No: ASTA-TYPE-0001175	Project No:	5104669077LCS004 Certificate No: ASTA-TYPE-0001177	g TECHN	O ELECTRO POWER INDUSTRIAL W.L
	wer industrial W.L.I., Building No. 765, Road 4811, Block No. 948, nama: Kinedom of Bahrain.		echno Electro Power Industrial W.L.I, Building No. 765, Road 4811, Block No. 948, hasary Area. Manama. Kinedom of Bahnain.	CAL	
Apparatus: 230V/500V/4kV a single-phase I incoming 2P lob	U ₄ /U ₂ /U ₄ , SOIIs switches and controlgenr assembly incorporating scienceal busines system with brass neutral link system, with one for unit, two 2P ELCB units, 16 SP outgoing MCB units and a brass link	Apparatus:	159/5009/44V ($U_s^{(i)}/U_{m_{ph}}$, 50Hz switchgear and controlgear assembly incorporating three-phase vertical bucker system with brass neutral link system, with one incoming P loadstar unit, how 4P EUG unit, 45 SP outgoing MCB unit, 17 SP	TECHN	BUILDING 765, ROAD 4811, BLOCK 948, LHASSAY AREA, KINGDOM OF BAHRAIN
	wer Industrial W.I.I., Building No. 765, Road 4811, Block No. 948, nama. Nindom of Bahrain.	Manufactured By:	nd a brass link protective circuit. Iechno Electro Power Industrial W.L.I., Building No. 765, Road 4811, Block No. 948, hasaw Area, Manaraa, Xinedom of Bahrain.		been found to conform to the Quality Management System standard:
Test Report No: 2007.22.02		Test Report No: 2	007.22.04		
Designation: 100A (10+6 Way	SPN Distribution Board	Designation: 3	DDA (10+6 Way)	E I	ISO 9001:2015
The apparatus which is representativ been evaluated in accordance with:	of the designation, supplied drawings and photographs has	The apparatus which is been evaluated in acco	representative of the designation, supplied drawings and photographs has dance with:	ТРАНИЧТ Тhis с Ма	certificate is valid for the following scope of operations:
IEC 61439-3: Edition 1.0, 2012-02, cli	zies 10.2 to 10.5 & 10.9 to 10.13	IEC 61439-3: Edition 1.	0, 2012-02, clauses 10.2 to 10.5 & 10.9 to 10.13	ž	
Verifications with reference to the tests list	d in Annex D of IEC 61439-1: Edition 2.0, 2011-08	Verifications with reference	e to the tests listed in Annex D of IEC 61439-1: Edition 2.0, 2011-08	Mai Mai	nufacturing of Techno Electro Power" PVC Conduits & Fittings,
1: Strength of material and parts	6/7/% No verification by testing required	1: Strength of material and	d parts 6/7/8: No verification by testing required	5	Panels, Distribution Boards, Control Panels, Gl Electrical Cable Tray, Gl Electrical Cable Trunk, Switch Disconnector and
2: Degree of protection of enclosures	9: Dielectric properties	2: Degree of protection of	enclosures R Dielectric properties	 J///// 	Changeover in Enclosure.
3: Gearances	10: Temperature-rise limits	2 Gearances	22: Temperature-rise limits		
4: Creepage distances	11: Short-circuit withstand strength	4: Creepage distances	11: Short-circuit withstand strength	μ (//////	
5: Protection against electric shock and int	grity of protective circuits 12: Electromagnetic compatibility (EMC) 13: Mechanical operation	5: Protection against elect	ric shock and integrity of protective circuits 12: Electromagnetic compatibility (EMC) 13: Mechanical operation	Date of hiddal region	:: Certificate No :: BH56861A uton Date of this Certificate Sure, andit on or before / Certificate expire Reco
is considered to comply with the above : stated on the ratings page(s) of this	a attached howths. The values obtained and the general performance andred(s) and to justify the noting assigned by the mexulationer as definited. This conflictes applies only to the appendux tested aparatus having the same or other designations rests with the	is considered to comply a stated on the ratings p	he record of tests attached hereits. The values obtained and the general performance with the above Kandard(t) and to justify the ratings assigned by the munificatorer as angel/of this Carthon. This correlation applies only to the separatant tested. mitry of any apparatus having the same or other designations rests with the	Date of Initial region 17 April 2024	
	Certification Engineer Abdul Majd Certification Officer Robert Huward		UKAS	IKAT	Director 2000 - Director

07



Dimensions & Diagram Please contact your nearest TEP sales office for drawings in printable format.

the sea



TECHNO ELECTRO POWER INDUSTRIAL W.L.L. Building 765, Road 4811, Block 948, Lhassay Area, Kingdom of Bahrain **M** +973 3975 9175 • **T** +973 1761 0046

info@tepgi.com



